



ARCHITECTURAL VINYL FABRIC FEATURES



Small variances in color are within commercial tolerances and should be anticipated.

18 OZ. ARCHITECTURAL VINYL FABRIC

- Durable– Excellent abrasion resistance and long life expectancy.
- Mildew resistant– Double mildewcide system and wick resistant scrim assure maximum protection
- Popular high-gloss finish and flat substrate give the high impact appearance and easy maintenance desired in today's market
- UVI resistant– premium outdoor vinyl formulation means vinyl stays softer.
- 18 oz. per sq. yd.
- 100% Recyclable
- Tensile Strength (warp/weft) 270/240 lbs./inch
- Tear Strength (warp/weft) 40/30lbs
- Flame Retardant– Method 1/NFPA 701-CSFM T19-Class A/ASTM E84-CAN/ULC S109-M2/NFP 92-507-M2/UNE 23.727-90-B1/DIN 4102-1-B1/ONORM A 3800-1-BS 7837-Class 1/UNI 9177-87-VKF 5.3/SN 198898-G1/GOST 30244-94-UBC 31-1-Group1/AS/NZS 3837-1530.3/AS/NZS-B-s2,d0/EN 13501-1

EQUINE CONCEPTS, LLC

Deming, WA 98244

Phone: 206-650-3312

Phone: 206-619-9378

E-mail:

equineconcepts@yahoo.com

www.equineconceptsllc.com